

Configuration			Revision					
Dash #			ECO	Rev.	Description	Date	Approv ed	
•	•			Α	Production release.	2/19/10	MKN/BAW	
			5414		Updated TSO reference. Assembly 9016978-3 was 9016978-6.	6/18/10	MKN/JDS	
			5531	С	Rotated Nameplate 180° and Warranty Decal 90°.	12/27/10	MKN/ScH	
<u> </u>	28VDC NPUT ONLY	5562	D	Env. Qual. Changed from(SM)to(SM/UG)	03/01/11	MKN/CJM		
		Logo and company name have been changed in title block only. No functional of technical changes have been made. Revision remains unchanged						





CONTEST ONE TO
TAWS WARN O TAWS CAUT TAWS NA G
MODE NODE NUTE TAWS INHB

Connector Pinout						
Pin#			Pin #			
1	Annun. Full Bright #1		14	Reduced Protection Mode* IN		
2	Annun. Full Bright #2		15	Reduced Protection Mode* OUT		
3	TAWS Warning BRT/DIM IN		16	Mute Caution* OUT		
4	Internal Dimming Program #1		17	Reserv ed		
5	TAWS Caution Annun.* IN		18	Reserv ed		
6	TAWS Test* IN		19	TAWS Annun. Inhibit* IN		
7	Annun. BRT/DIM IN		20	TAWS Inhibit* OUT		
8	Panel Lighting Bus HI**		21	Aircraft Ground		
9	Panel Lighting Bus LO		22	Aircraft Ground		
10	TAWS Not Available Annun. IN		23	Aircraft Ground		
11	TAWS Warning Annun.* IN		24	Aircraft Ground		
12	Internal Dimming Program #2		25	Aircraft Ground		
13	Aircraft Power**					

Description

Nameplate

Decal, Warranty

Assy, MD41-1048(5V)

Decal, 28VDC For MD41

Designates an active low signal

Item Qty Part Number

1 9016978-3

1 7016942

1 9017000

See Specifications for lighting voltage input.

Specifications						
Power Input	28 VDC 0.15 Amps					
Lighting	LEDs; 5 VDC input					
Dimming	Automatic or Full Bright					
Weight	0.26 lbs					
	FAA TSO C151					
Qualification Tests	RTCA DO-160					
	Env. Cat. F2CAB(SM/UG)XXXXXXZBABA(TT)M[A3C3]XXA					
Temperature	-55°C to 70 °C					
Altitude	0 to +55,000 Ft.					
Connector	MD25M5R40V30					
Mating Connector	RD25F10JVL0					
	Bezel: Black					
	TAWS WARN Annuncation: Red					
Color	TAWS CAUT and TAWS N/A Annuncations: Amber					
	RP MODE and TAWS INHB Annunciations: White					
	Buttons: Backlit White					

				4	1	6018956		
	UNLESS OTHERWISE SPECIFIED, ALL DIMENSIONS ARE IN INCHES. TOLERANCE: FRACTIONAL=±1/64 .XX=±0.015	DRAWN: MKN 11/17/2009	This document discloses proprietary information of Mid-Continent Instrument Co. It may be reproduced or disclosed only with written permission of Mid-Continent Instrument Co. a is not to be used in any way detrimental to the interests of Mid-Continent Instrument Co.					
	.XXX=±0.005 .XXXX=±0.002	APPROVED:	TITLE:					
CON	ANGULAR=±0.5°	BAW	HTAWS Annunciation U					

SCALE: 2:3

2/18/2010

CONCENTRICITY: 0.005 TIR BREAK ALL SHARP EDGES THREADS PER MIL-S-7742

MidContinent TINSTRUMENTS + AVIONICS

PART NUMBER: MD41-1048(5V) **HTAWS Annunciation Unit** DO NOT SCALE THIS DRAWING SHEET: 1 of 1